

Monessen Vent Free Gas Fireplace Systems and Inserts

CONVENIENT OPTIONS TO FIT YOUR STYLE





Parlor Series

CHOOSE THE FIREPLACE THAT'S RIGHT FOR YOU

Our Monessen vent free fireplace lineup offers flexible installation and a lineup so versatile, you're sure to find the model that's right for you. We've got everything from compact models, perfect for smaller rooms, to larger models with more heating power. Check out the advantages of a vent free fireplace from Monessen below:

MAXIMIZE SAVINGS WITH HIGHEST EFFICIENCY

Vent free gas fireplaces, available in natural gas and propane designs, are a safe, green and energy efficient way to add heat to your home – in fact, they're 99.9% energy efficient. Because they are vent free, none of the heat gets lost up a vent, flue or chimney. Instead, fuel dollars get transformed into heat-warming energy. Plus, you'll always have the assurance of a heat source in the event of a power outage.

FREEDOM TO INSTALL ALMOST ANYWHERE

Because vent free fireplaces are designed to be installed and operated without a chimney, flue or vent, they can be installed in locations in your home where it would be impossible to install a vented fireplace. They provide the most economical installation, only requiring a connection to a gas line.

ZERO CLEARANCE FOR ULTIMATE FLEXIBILITY

Monessen vent free fireplaces allow for zero clearance installation, which means they may be installed flush against any combustible surface such as drywall or wood. This gives you added flexibility and helps save installation dollars when deciding where to install your fireplace, whether on an interior or exterior wall, or even in a corner.

(It is important to remember that the appliance should be sized to fit the area in which it is to be installed and must meet any additional regional or local requirements.)

Pictured on cover:
Chesapeake Series



TAKE HOME A BEST-SELLER

Chesapeake CFX Vent Free Gas System

This best-selling model comes complete with firebox, strikingly realistic log set, decorative filigree and beautifully crafted Barrington cabinet — all ready to install! With the Chesapeake vent free system, it's never been easier to make your house a home.

Quick Look:

- Triple Play Burner System® with loose embers glowing logs and yellow flames
- Your choice of Dark Walnut or Unfinished Cabinet
- Decorative filigree comes standard
- Up to 26,000 BTUs
- Available in 24" and 32" sizes
- Millivolt control (remote ready)

Interior Firebrick (Optional)



Cottage Clay
Firebrick
(shown on cover)

Trim Options



Dark Walnut Cabinet
(shown)



Unfinished Cabinet



DFS Series



DFS Series

STAY WARM AND COZY

DFS Series

This full-size fireplace system provides ample heat for large rooms and also offers a variety of finishing options for a custom look.

Quick Look:

- Triple Play Burner System® with loose embers, glowing logs and yellow flames
- Removable unitized louver system
- 38,000 - 26,000 BTUs
- Fixed screen
- Concealed controls
- Black trim kit & louvers
- Available in 32", 36" and 42" sizes
- Millivolt control (remote ready)

Interior Firebrick Options



Cottage Red Firebrick



Cottage Clay Firebrick (shown)

Trim Options



Stainless Steel Trim



Black Trim



Classic Faces

Additional Trim Option

Optional radiant panel kits

Cabinet Options



Honey Oak Wall or Corner Cabinet



Barrington Dark Walnut Wall Cabinet



Unfinished Birch Wall Cabinet
(Available in corner styles by special order.)



Dark Cherry Wall or Corner Cabinet



Barrington Unfinished Wall Cabinet



Unfinished Oak Wall Cabinet
(Available in corner styles by special order.)

< Wall Cabinet shown in Honey Oak
Also available in corner style

BEDROOM APPROVED!

DBX Series

Featuring a one-piece, two-log design with thermostat control, this fireplace system is ideal for adding the ambience of a beautiful fire to a smaller area.

Quick Look:

- Yellow Flame burner system
- Ceramic fiber log set
- 10,000 BTUs*
- Available in 24"
- Built-in thermostat control
- Removable unitized louver system
- Includes black trim & louvers
- All cabinet options available in wall and corner configurations

Interior Firebrick



Cottage Clay Firebrick

Cabinet Options



Honey Oak Wall or Corner Cabinet



Dark Cherry Wall or Corner Cabinet



Unfinished Oak Wall Cabinet
(Available in corner styles by special order.)

*Per national codes, 10,000 BTUs is the maximum heat output from a vent free gas fireplace permitted in a bedroom installation.



DBX Series

SMALL IN SIZE, BIG IN HEATING CAPABILITY


DFX Series

With its compact design, the DFX fireplace system is perfect for smaller rooms and provides up to 26,000 BTUs of heating power.

Quick Look:

- Triple Play Burner System® with loose embers, glowing logs and yellow flames
- Ceramic fiber log set
- 26,000 - 22,000 BTUs
- Available in 24" or 32" sizes
- Removable unitized louver system
- Millivolt control (remote ready)
- Includes black trim & louvers
- All cabinet options available in wall and corner configurations

Interior Firebrick



Cottage Clay Firebrick

Cabinet Options



Honey Oak Wall or Corner Cabinet



Dark Cherry Wall or Corner Cabinet



Unfinished Oak Wall Cabinet
(Available in corner styles by special order.)



Barrington Dark Walnut Wall Cabinet



Barrington Unfinished Wall Cabinet



DFX Series

NO CORNER LEFT BEHIND

Parlor Fireplace System

The unique and versatile design of this system is a perfect solution for smaller spaces and corners where a traditional fireplace won't easily fit. With multiple face and brick options, this is a great way to add ambiance to any room.

Quick Look:

- Ceramic fiber log set
- Available in 20" Size
- 20,000 BTUs
- Millivolt control (remote ready)
- Accent light with manual control

Interior Liner Options




Grey Cobbled Fieldstone (shown)



Tuscany Firebrick



Cobbled Fieldstone Firebrick



Adobe Arched Firebrick



Parlor Series shown with unfinished wall cabinet painted white



Parlor Series shown with Dark Walnut corner cabinet

Decorative Face and Screen Options



Colonial Arch in Iron Age



Classic Arch in Textured Black



Colonial Arch in Textured Black



Decorative Screen Front



Dark Walnut Cabinet (Available in wall and corner models; also available unfinished)

———— All Parlor Arches are available in both Textured Black and Iron Age ————

Optional Accessories

	CFX	DFS	DBX	DFX	PL	DIS
Cottage Clay Firebrick	X	X	X	X		
Cottage Red Firebrick		X				
Arched Firebrick					X	
Stainless Steel Louvers		X				
Black Face Plate			X			X ²
Black & Stainless Steel Curved and Medium Trim		X				
Classic Faces		X				
Parlor Faces					X	
Corner/Wall Cabinets	Standard	X	X	X	X	
BLO24TB			X			
BLO24T	X ¹			X ¹		
BLOT	X ¹	X		X ¹		
Multi-functional Ambient Technologies® Remote Controls	X	X		X	X	X

1) DFX32 and CFX32 take BLOT, DFX24 and CFX24 take BLO24T

2) DIS Black Face Plate is available in two sizes: 43"W x 33"H or 50"W x 36"H

GIVE YOUR MASONRY FIREPLACE A FACE LIFT

DIS Insert Series

A great way to convert your wood burning masonry fireplace into a more efficient heating system, this easy-to-install vent free insert fits most standard masonry fireplaces with a minimum opening of 24" high, 33" wide and 16 1/2" deep. With 28,000 BTUs, it keeps up to 950 square feet warm and cozy.

Quick Look:

- Triple Play Burner System® with loose embers, glowing logs and yellow flames
- Charred Timber log set
- 28,000 BTUs
- Millivolt control (remote ready)
- Removable unitized bottom louvers
- Standard blower

Interior Firebrick



Cottage Clay Firebrick (shown)

Trim Options






Black Face Plate (2 sizes)
Available in two sizes to attractively finish the gap between the masonry fireplace and the DIS Insert. Face Plate dimensions are: 43 1/2" W x 33" H and 40 1/4" W x 36" H. At minimum, the face plate should extend at least 1/2" over the masonry opening.



DIS Insert Series

Cabinet Dimensions

Product	Surround	A	B	C	D	E	F	G	H	I			
Standard Wall Cabinet Mantels (Hearth Included with Cabinet)													
DBX24, DFX24	WSH24	38 1/8"	14 7/8"	38"	13 3/4"	26 1/4"	24 3/4"	26 5/8"	35 5/8"	6 7/8"			
DFX32	WSH32	52"	16 3/4"	48 1/4"	13"	34 1/8"	32 3/4"	30 7/8"	44 5/8"	6 7/8"			
DFS32	WSHGC32	57 3/4"	21"	49 3/4"	18"	39 1/4"	37 3/4"	35 7/8"	52 1/4"	5"			
DFS36	WSHGC36	61 1/2"	22 1/4"	49 3/4"	19 3/8"	43 1/4"	41 3/4"	35 7/8"	56 1/4"	5"			
Standard Corner Cabinet Mantels (Hearth Included with Cabinet)													
DBX24, DFX24	CSH24	46"	32 1/2"	26 3/4"	38"	26 1/4"	24 3/4"	26 5/8"	36"	13 3/4"			
DFX32	CSH32	56 3/8"	40"	32 5/8"	48 1/4"	34 1/8"	32 3/4"	30 7/8"	43 1/4"	18 5/8"			
DFS32	CSHGC32	62"	43 7/8"	35 5/8"	49 3/4"	39 1/4"	37 3/4"	35 7/8"	57 1/4"	5"			
DFS36	CSHGC36	67 1/2"	47 3/4"	39 1/8"	49 3/4"	43 1/4"	41 3/4"	35 7/8"	63"	5"			
Barrington													
DFX24, CFX24	BWC300	52 1/2"	15"	44"	34 3/8"	5"	47 5/8"	30"	-	-	Max adj opening WxH 26 1/2" X 27"	Min adj opening WxH 24" X 23 1/2"	Max fireplace depth 10 1/2"
DFX32, CFX32	BWC400	61 9/16"	18"	50 3/4"	34 3/8"	5"	47 5/8"	30"	-	-	35 1/2" X 32 3/4"	32" X 29"	14"



Vent Free Gas Fireplace Systems

	CHESAPEAKE CFX24	CHESAPEAKE CFX32	
BTR/HR	22,000 - 17,000 NG / 22,000 - 17,000 LP	26,000 - 20,000 NG / 26,000 - 20,000 LP	
Actual Dimensions (Inc Cabinet)	52 1/2"W x 44"H x 15"D	61 9/16"W x 50 3/4"H x 18 1/4"D	
Viewing Area	19 3/4" W x 11 3/4" H (232 sq in)	26" W x 15 1/4" H (396 sq in)	
Blower	Optional	Optional	
	DFS32C	DFS36C	DFS42C
BTR/HR (Millivolt Control)	38,000 - 26,000 NG / 34,000 - 26,000 LP	38,000 - 26,000 NG / 34,000 - 26,000 LP	38,000 - 26,000 NG / 34,000 - 26,000 LP
Dimensions (Actual)	37"W x 34 1/2"H x 18 5/8"D	41"W x 34 1/2"H x 20 5/8"D	47"W x 34 1/2"H x 20 5/8"D
Dimensions (Framing)	37 1/2"W x 35"H x 15 3/4"D	41 1/4"W x 35"H x 17 3/4"D	47 1/4"W x 35"H x 17 3/4"D
Front Opening	29 7/8" W x 21 3/4"H	34" W x 21 3/4"H	40" W x 21 3/4"H
Radiating or Circulating	Both	Both	Both
	DFX24C	DFX32C	DBX24C
BTR/HR (Millivolt Control)	22,000 - 17,000 NG / 22,000 - 17,000 LP	26,000 - 20,000 NG / 26,000 - 20,000 LP	
BTR/HR (Thermostat Control)	—	—	10,000 NG & LP
Dimensions (Actual)	24 1/2"W x 26 1/2"H x 11 7/8"D	32"W x 30"H x 13 3/8"D	24 1/2"W x 26 1/2"H x 11 7/8"D
Dimensions (Framing)	24 3/4"W x 26 3/4"H x 10 1/2"D	32 1/2"W x 30 1/4"H x 12 1/4"D	24 3/4"W x 26 3/4"H x 10 1/2"D
Viewing Area	20" W x 11 3/4" H (234 sq in)	26" W x 15 1/4" H (396 sq in)	20" W x 11 3/4" H (234 sq in)
	PARLOR PL20NV		
BTR/HR	20,000 - 14,500 NG/20,000 - 17,000 LP		
Dimensions (Actual)	19 1/2"W x 31 7/8"H x 10 5/8"D		
Dimensions (Framing)	20"W x 32 1/8"H x 10 1/16"D		
Fireplace Opening	17 1/4"W x 22 1/2"H		
	DIS (INSERT ONLY)	SMALL FACE PLATE	LARGE FACE PLATE
BTR/HR	28,000 - 19,000 NG / 28,000 - 23,000 LP	—	—
Dimensions (of Front)	33"W x 26 3/4"H x 16 1/2"D	43 1/4"W x 33"H	50 1/4"W x 36"H
Minimum Firebox Opening	33 1/2" W x 27 1/2" H x 16" D x 22 3/4" RW	—	—
Viewing Area	27" W x 14 1/2" H (392 sq in)	—	—
Heating Area	950 sq. ft	—	—

Accessories

Remotes and thermostats are available for all millivolt control models for added convenience.



LOVE AT FIRST LIGHT

A brand of Monessen Hearth Systems Co.
149 Cleveland Drive, Paris, Kentucky 40361
monessenhearth.com

Your Monessen Dealer:



To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice.
©2011 Monessen Hearth Systems Co. 11031_0911

For more information about MHSC and Monessen efficient and environmentally friendly products, please visit monessenhearth.com

MON820B Ver8